

# SMARTOP UPRIGHT 2.0 OPERATING INSTRUCTIONS



Red Pull to Release Bar

- 1) Open cover and fold in half using the EAS Lift and Assist system.
- 2) The best way to lift the cover completely off the spa is to enter the hot tub and push the cover up from the center.
- 3) You can also lift the cover by standing outside the hot tub. Grab on to the handle of the EAS Lift and Assist after the cover has been folded in half and start pushing upward. The hydraulic shocks will do most of the work to bring the cover to a fully opened position and lock the cover in place.
- 4) To close the cover from inside the spa, **pull on the red PULL TO RELEASE bar on the locking shock** and pull the cover down until it is resting on the sides of the spa.  
**NOTE: Damage to the cover can occur if the locking mechanism is not disengaged.**
- 5) To close the cover from outside the spa, get out of the hot tub and go to the side of the spa that has the Pull to Release shock. **The cover should not be closed until the locking mechanism on the shock has been disengaged** or cover lift damage can occur. **Pull on the red PULL TO RELEASE bar on the locking shock**, grab on to the handle of the EAS Lift and Assist and pull the cover down until it is resting on the spa.
- 6) The hydraulic shocks will do most of the work to bring the cover to a closed position. Fold the top half of the cover back onto the spa. Position the spa cover on the spa, making sure that all four corners are properly positioned and square on the spa. **Lock down your cover to prevent wind damage.**
- 7) **Do not use the Smartop in high wind conditions.** Injury from the spa cover being blown over and impacting the spa user can occur.